

APDatec 910 natur

Single layer Polyamide tube of PA 11/12

- Applications** pneumatics, vehicle construction, compressors, automation technology & robotics, compressed air
- Structure** PA, uncolored, translucent
- Temperature** -40°C up to 90°C
- Properties** good temperature resistance, , smooth outside, smooth inside



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
2	4,00	1,00	20	40,00	0,01000	1,00	100	9100041000
3	5,00	1,00	25	35,00	0,01350	1,35	100	9100051000
4	6,00	1,00	30	25,00	0,01600	1,60	100	9100061000
5	8,00	1,50	40	25,00	0,03200	3,20	100	9100081500
6	8,00	1,00	40	20,00	0,02260	2,26	100	9100081000
8	10,00	1,00	60	15,00	0,03000	3,00	100	9100101000
9	12,00	1,50	75	17,00	0,05300	5,30	100	9100121500
10	12,00	1,00	60	13,00	0,03600	3,60	100	9100121000
12	15,00	1,50	90	15,00	0,06200	6,20	100	9100151500